



Kimitech TNT

ST3-0221

Non-woven fabric to reinforce waterproofing and protective liquid resins of Kimitech and Kimicover ranges

DESCRIPTION

Kimitech TNT is a nonwoven continuous filament based on heat-sealed two-component filaments with PET core and PP coating, characterized by a high chemical resistance in alkaline environments and by an excellent mechanical resistance combined with a remarkable ductility.

USES

Reinforcing mesh of waterproofing systems **Kimicover**.

APPLICATION

For different kind of works read the technical specifications and the technical data sheets of the materials to be used. It is used on planar surfaces. It is not suitable for use on corner surfaces (use the mesh Kimitech 120 for these points).

PACKAGING

Rolls:

- Width 100 cm.
- Length 100 or 25 m.

Characteristics	Typical value
Grammage [g/mq]	100
Thickness [mm]	0,7
Failure tension [N/5 cm]	240
Elongation at failure [%]	67

WARNING

Product for professional use.

The product is an item according to the definitions of Regulation (EC) n. 1907/2006 and therefore does not require a Safety Data Sheet.

The marking obligations are not related to the intrinsic nature of a given product, but to the use to which a specific material is intended: before making the order in Kimia, the buyer shall submit all the documentation available to the works supervision in order to determine the materials

suitability (in terms of certifications and performance) in relation to the use for which they are intended.

The information and requirements indicated in this Technical Data Sheet are based on our current knowledge and experience and are to be considered, in any case, purely indicative. They cannot guarantee the final result of the applied product and they have to be confirmed by exhaustive practical applications; therefore the user must test the suitability of the product for the intended application and its purpose. Users must always refer to the latest version of the local technical data sheet related to the product.