



Kimitherm ALU Start

ST3-0221

Aluminium starting profile



DESCRIPTION

Kimitherm ALU Start is a starting profile, with ending section shaped as a drip channel. It is available in different sizes depending on the thickness of the insulating panels. It is compliant and certified according to the requirements of the ETAG004 for insulation panels for external insulation systems.

USES

Kimitherm ALU Start is designed as a horizontal starting element for the installation of insulating panels in the process of bonding to the wall in insulation coat systems.

STORAGE

The product fears humidity. Store in a sheltered and dry place, in these conditions and in intact containers, the product maintains its stability for 12 months.

exhaustive practical applications; therefore the user must test the suitability of the product for the intended application and its purpose. Users must always refer to the latest version of the local technical data sheet related to the product.

Measures [mm]	Packaging	Pallet
60 x 2500	25 m	925 m
80 x 2500	25 m	1175 m
100 x 2500	25 m	800 m
120 x 2500	25 m	400 m

WARNING

Product intended for professional use. The marking obligations are not related to the intrinsic nature of a given product, but to the use to which a specific material is used: before making the order in Kimia, the buyer shall submit all the documentation available to the construction supervision in order to determine the materials suitability (in terms of certifications and performance) in relation to the use for which they are intended. The information and requirements indicated in this Technical Data Sheet are based on our current knowledge and experience and are to be considered, in any case, purely indicative. They cannot guarantee the final result of the applied product and they have to be confirmed by