

Kimitherm DROP PVC

ST2-0221

Drip edge profile



DESCRIPTION

Kimitherm DROP PVC is a corner "claw corner" with heat-welded fiberglass mesh. The plastic profile is visible, and is protected by a strip which can be removed after skimming and painting of the surface.

It is compliant and certified according to the requirements of the ETAG004 for insulating panels for external insulation systems.

USES

Kimitherm DROP PVC it is used to reinforce and protect horizontal corners (lintels, balconies, string courses, cantilever elements, etc.), it is a dropbreaker. It is paintable.

STORAGE

The size of the item are: 100x100x2500 mm.

The product fears humidity. Store in a sheltered and dry place; in these conditions and in unopened containers, the product maintains its stability for 24 months.

WARNING

Product intended for professional use.

The marking obligations are not related to the intrinsic nature of a given product, but to the use for which a specific material is used: before ordering in Kimia, it will be the customer's responsibility to submit all the available documentation to the construction supervision so that they can establish the suitability of the materials (in terms of certifications and performance) in relation to the use for which they are intended.

The information and requirements indicated in this Technical Data Sheet are based on our current knowledge and experience and are to be considered, in any case, purely indicative. They cannot guarantee the final result of the applied product and they have to be confirmed by exhaustive practical applications; therefore the user must test the suitability of the product for the intended application and its purpose. Users must always refer to the latest version of the local technical data sheet related to the product.